



IPSO®

Semi-commercial washer

FW60

Semi-commercial dryer

FD112 - FDC112 - FDHP112



Features

WASHER-EXTRACTORS

- White cabinet
- Stainless steel drum and tub
- Easy to use timer
- Mop and medical programs
- Soap hopper at the front
- Matching dryer available – space saving when placed on top

DRYERS

- White cabinet
- Stainless steel drum and tub
- Large door opening (Ø45 cm)

Options

WASHER-EXTRACTORS

- External coin meter
- Drain valve
- Liquid soap pumps
- Marine voltages available

DRYERS

- External coin meter
- Condens unit (FDC112)
- Heat pump heating (FDHP112)
- Marine voltages available



COMPACT
DESIGN



STACKABLE
UNIT



LOW ENERGY
CONSUMPTION



FW60

Drum	
Capacity	6 kg
Volume	60 l
Diameter	480 mm
Drum speed	
Extraction speed	1600 rpm
G-factor	690
Heating	
Electrical	3,2 kW
Connections	
Electrical	200V/50-60Hz/1 230V/50-60Hz/1 400-415V/50-60Hz/3+N 400-440V/60Hz/3
Water	3/4"
Circuit breaker	230V-10A / 400V-16A
Drain	
	Pump standard, drain valve optional
Transport data	
Gross weight	78 kg
Net weight	76 kg
Dimensions HxWxD	850x595x585 mm
Packing dimensions HxWxD	920x640x660 mm

FD 112 vented dryer

FDC 112 condense dryer

FDHP 112 heat pump dryer

	FD 112 vented dryer	FDC 112 condense dryer	FDHP 112 heat pump dryer
Drum			
Capacity	6 kg	6 kg	6 kg
Volume	112 l	112 l	112 l
Diameter	571 mm	571 mm	571 mm
Heating			
Electrical	3 kW	2,5 kW	-
Connections			
Electrical	200V/50-60Hz/1 230V/50-60Hz/1 400-415V/50-60Hz/3+N 400-440V/60Hz/3	200V/50-60Hz/1 230V/50-60Hz/1 400-415V/50-60Hz/3+N 400-440V/60Hz/3	200V/50-60Hz/1 230V/50-60Hz/1 400-415V/50-60Hz/3+N 400-440V/60Hz/3
Circuit breaker	230V-10A / 400V-16A	230V-10A / 400V-16A	230V-10A / 400V-16A
Airflow	123 m³/h	123 m³/h	123 m³/h
Air evacuation	100	-	-
Transport data			
Gross weight	42 kg	46 kg	54 kg
Net weight	40 kg	44 kg	52 kg
Dimensions HxWxD	850x595x585 mm	850x595x585 mm	850x595x585 mm
Packing dimensions HxWxD	920x640x660 mm	920x640x660 mm	920x640x660 mm