



INDUSTRIAL TUMBLE-DRYER

I190
9 KG

FEATURES


- Standard stainless steel drum with large diameter
- Easy-to-use microprocessor (ECT)
- Innovative bulged drum
- Combination of radial and axial airflow
 - maximal heat transfer
 - low energy consumption
 - short drying time
- Large door opening for easy loading and unloading

OPTIONS

- Reverse drum
- Full control programmer
- Residual moisture control
 - safe drying of delicate linen
 - humidity detection in %
 - ideal in combination with Softwash®
 - Ideal for dry cleaners, fire departments
 - available on Easy and Full Control
- Stainless steel front



LARGE DOOR
OPENING



ENERGY
EFFICIENT



STANDARD
STAINLESS
STEEL DRUM

THE SMART LAUNDRY PARTNER

	1190
DRUM	
CAPACITY	9
VOLUME (L)	190
DIAMETER (MM)	Ø760
DRYING PERFORMANCE	
AIRFLOW (M ³ /H)	350
DRYING AVERAGE (L/MIN)	0,150
GAS HEATING	
GAS CONNECTION (IN)	3/4"
ELECTRICAL CONNECTION	3x380-415V 50/60Hz, 3x220-240V 50Hz, 3x208-240V 60Hz, 3x440V 60Hz
ENERGY (KW)	12,5
ENERGY (kBTU/H)	42,7
ELECTRICAL HEATING	
ELECTRICAL CONNECTION	3x380-415V 50/60Hz, 3x220-240V 50Hz, 3x208-240V 60Hz, 3x440V 60Hz, 3x480V 60Hz
ENERGY (kW)	9/12
MOTOR	
FAN (KW)	0,37
DRIVE (KW)	0,18
CONNECTION	
EXHAUST (MM)	Ø150
PROGRAMMER	
EASY CONTROL - antivandal (ECT)	Standard
FULL CONTROL	Available
DIMENSIONS	
H X W X D (MM)	1465 x 795 x 815
NET WEIGHT (KG)	170
TRANSPORT DATA	
PACKED H X W X D (MM)	1570 x 880 x 885
GROSS WEIGHT (KG)	180

The data concerning dimensions of machines include all extended parts

